

1400KW 1500KW 2000KW 60Hz Sound proof Cummins container generator set

Specifications :

Price	41000-150000
Brand Name	CHINLION
Model Number	CHLCS1500D6S
Place of Origin	CHINA
Min.Order Quantity	1
Payment Terms	T/T L/C
Supply Ability	45days
Delivery Detail	30days
Packaging Details	Wood

Detail Introduction :

Genset Power	1619.0
Model Type	Soundproofed
Engine Model	KTA50-G9
Alternator Model	PI734B
Control System Model	PLC-7420
General Data	CHLCS1500D6S
Manufacturer	CHINLION
Prime Power?kVA?	1619.0
Standby Power?kVA?	1875.0
Prime Power?kW?	1295.0
Standby Power?kW?	1500.0
Power Factor	0.8
Frequency?Hz?	60.0
Phase	3.0

Wires	5.0
Volatage?V?	416/440/460/480
Fuel Consumption (75%load)?L/h?	257.0
Fuel Consumption (100%load)?L/h?	330.0
Fuel Tank Capacity?L?	2500.0
Oil Consumption?L/h?	0.25
Displacement?L?	50.3
Noise Level@1m?dBA?	100.9
Noise Level@7m?dBA?	94.1
Dimensions L*W*H?mm?	12192*2438*2896
Dry Weight?Kg?	25000.0
Type of Fuel	0# or ASTM2
Type of Oil	CF4/SG15W-40
Machine Body	
Model Type	Soundproofed
Length?mm?	12192.0
Width?mm?	2438.0
Height?mm?	2896.0
Protection Level	IP54
current	
380V / 400V / 415V / 440V	/
208V/220V / 230V / 240V	/
416V / 440V / 460V / 480V	2247/2124/2032/1947
6000V~6600V	/
10000V~13800V	/
Genset Control Cabinet	
Control Model	PLC-7420

Starting Type	Auto/Manual
Screen Display Mode	
Screen Dimension?mm?	240*181*41.7
Observation Window and Control Door	?
Protection Level	IP56
Battery Charger	?
Breaker	ABB 2500A
Poles	3.0
Breaker Control Mode	Manual
Leak Protection Device	X
Connection Type of External Cable	Connector bar
Cable Line Slot	X
Genset Internal Connection Type	X
Fuel Tank	
Fuel Tank Capacity?L?	2500.0
Injection System	Direct injection
Recommended Fuel Type	0# or ASTM2
Fuel Tank Type	Double-layer
Can be connected to external fuel filling device	?
Fuel Tank Drain	?
Fuel Level Control Panel Display	?
Fuel Level Gauge	?
Auto Refilling Diesel System	X
Oil Pan	X
Fuel Three-way Valve	?
Conditions	
Ambient Temperature ?°C?	40.0

Barometric Pressure ?kPa?	100.0
Relative Humidity	?80%
Altitude ?m?	?1000
Genset Power	1706.0
Model Type	Soundproofed
Engine Model	QSK50-G4
Alternator Model	PI734C
Control System Model	PLC-7420
General Data	CHL1500D6S
Manufacturer	CHINLION
Prime Power?kVA?	1706.0
Standby Power?kVA?	1875.0
Prime Power?kW?	1365.0
Standby Power?kW?	1500.0
Power Factor	0.8
Frequency?Hz?	60.0
Phase	3.0
Wires	5.0
Volatage?V?	416/440/460/480
Fuel Consumption (75%load)?L/h?	279.0
Fuel Consumption (100%load)?L/h?	363.0
Fuel Tank Capacity?L?	2500.0
Oil Consumption?L/h?	0.25
Displacement?L?	50.3
Noise Level@1m?dBA?	100.7
Noise Level@7m?dBA?	94.5
Dimensions L*W*H?mm?	12192*2438*2896

Dry Weight?Kg?	23560.0
Type of Fuel	0# or ASTM2
Type of Oil	CF4/SG15W-40
Machine Body	
Model Type	Soundproofed
Length?mm?	12192.0
Width?mm?	2438.0
Height?mm?	2896.0
Protection Level	IP54
current	
380V / 400V / 415V / 440V	/
208V/220V / 230V / 240V	/
416V / 440V / 460V / 480V	2368/2239/2141/2052
6000V~6600V	/
10000V~13800V	/
Genset Control Cabinet	
Control Model	PLC-7420
Starting Type	Auto/Manual
Screen Display Mode	
Screen Dimension?mm?	240*181*41.7
Observation Window and Control Door	?
Protection Level	IP56
Battery Charger	?
Breaker	ABB 2500A
Poles	3.0
Breaker Control Mode	Manual
Leak Protection Device	X

Connection Type of External Cable	Connector bar
Cable Line Slot	X
Genset Internal Connection Type	X
Fuel Tank	
Fuel Tank Capacity?L?	2500.0
Injection System	Direct injection
Recommended Fuel Type	0# or ASTM2
Fuel Tank Type	Double-layer
Can be connected to external fuel filling device	?
Fuel Tank Drain	?
Fuel Level Control Panel Display	?
Fuel Level Gauge	?
Auto Refilling Diesel System	X
Oil Pan	X
Fuel Three-way Valve	?
Conditions	
Ambient Temperature ?°C?	40.0
Barometric Pressure ?kPa?	100.0
Relative Humidity	?80%
Altitude ?m?	?1000