

Kingo Negative Pressure Ambulance

Specifications :

Price	21000-25000
Brand Name	kinglong
Model Number	CHL001
Place of Origin	CHINA
Min.Order Quantity	1
Payment Terms	T/T
Supply Ability	1000
Delivery Detail	40
Packaging Details	RORO

Detail Introduction :

Standard Configuration of the Kingo Negative Pressure Ambulance (Type I/Type II)

Item Vehicle Model Parameters

Vehicle Dimensions Length x width x height (mm) 5470x1885x2440; 5570x1885x2440 (with rear step)

Wheelbase (mm) 3110

Front/rear wheel track (mm) 1635/1745

Internal Dimensions of Medical Cabin Length x width x height (mm) 3360X1700X1570

Weight Parameters Curb weight (kg) 2150

Gross mass (kg) 3380

Trafficability Approach angle/departure angle (°) 17/18?17/17

Minimum turning diameter (m) 11.7

Dynamic Performance Maximum speed (km/h) 150

Maximum gradeability (%) ?30%

Engine Engine Model Mianyang Xincheng 4RB2

OBD Standard configuration

Emission standard China V for light vehicle

Operating mode In-line 4-cylinder 8-valve, variable valve timing technology

Displacement (mL) 2438

Rated power (kW/rpm) 102/4600~5000

Maximum torque (N·m/rpm) 210/2600~3200

Transmission Transmission model Yancheng Zomax (ZM025A)

Fuel Tank and Fuel Fuel type Gasoline

Fuel tank volume (L) 70

Steering System Steering assist Hydraulic power assisted steering, pinion-and-rack type

Brake System Type of brake system Hydraulic double-circuit vacuum boosting

Brake assist system Electronic ABS+EBD brake assist system (ABS + braking force distribution)

system)

Parking brake Side parking brake structure, with hand control acting on rear wheels

Suspension System Front suspension structure Front independent, torsion bar

Rear suspension structure Non-independent, steel plate, 5 springs

Wheel Model 195R/15C;195R/15LT

Quantity 5

Number of Seats Number of Seats 5-9

Note: Other configuration details are seen in the sales configuration table.

Special Configuration of the Kingo Negative Pressure Ambulance (Type I/Type II)

Function Equipment Equipment Description Quantity Used

Alarm Lamp System Alarm lamp Strip alarm lamp One set

Central Power Distribution System Multifunctional power supply control system It supports two power supply modes, external power supply (to be connected with utility power) and vehicle-mounted intelligent inverter power supply system, capable of automatic switching between 12 V DC and 220 V AC power supplies. One set

Medicine Cabinet System Medicine cabinet Light-weight environmental protection material One set

Oxygen cylinder cabinet Light-weight environmental protection material One set

Combined cabinet Light-weight environmental protection material One set

Medical Floor Medical floor leather Resistant to acid, alkali, fire, skidding, static electricity One set

Specialized Medical Equipment Oxygen cylinder 10L Two sets

Sputum aspirator One set

Sphygmomanometer One set

Ultraviolet disinfection lamp One set

Oxygen supply system One set

Stretcher System Deluxe automatic boarding stretcher + automatic boarding platform (including shovel stretcher) Patient transferring One set

Medical Cabin Lighting System Working lamp One set

Stretcher-type Negative Pressure Isolation Cabin Stretcher-type Negative Pressure Isolation Cabin

Power supply: rated voltage of AC 220 V, 50 HZ, internal power supply DC 12 V, input power of 50 VA. Filtration power: filtration efficiency ≥99.99% for 0.3 μm particulate aerosol. Negative pressure: A negative pressure of not less than 15 Pa shall be established within 2 min when there is passenger in the ambulance. Ventilation rate: ≥75 L/min. Effective power supply duration: lithium battery power supply, ≥2 h. Noise: ≤72 dB(A). One set

Negative Pressure System Fan system Exhaust air rate: 200 m³/h-600 m³/h, 220 V, 300 W to ensure optimal ventilation efficiency in the medical cabin, and to minimize the probability of cross infection among medical staff during the process of treating and transferring patients with infectious diseases. One set (Type II only)

Filtration system Filtration power: filtration efficiency ≥99.99% for 0.3 μm particulate aerosol (the national standard requiring ≥99.97%). The air in the van will be discharged after bio-safety disposal. Standard Configuration of the Kingo Negative Pressure Ambulance (Type I/Type II)

Item Vehicle Model Parameters

Vehicle Dimensions Length × width × height (mm) 5470×1885×2440; 5570×1885×2440 (with rear step)

Wheelbase (mm) 3110

Front/rear wheel track (mm) 1635/1745

Internal Dimensions of Medical Cabin Length × width × height (mm) 3360X1700X1570

Weight Parameters Curb weight (kg) 2150

Gross mass (kg) 3380

Trafficability Approach angle/departure angle (°) 17/18?17/17
 Minimum turning diameter (m) 11.7
 Dynamic Performance Maximum speed (km/h) 150
 Maximum gradeability (%) ?30%
 Engine Engine Model Mianyang Xincheng 4RB2
 OBD Standard configuration
 Emission standard China V for light vehicle
 Operating mode In-line 4-cylinder 8-valve, variable valve timing technology
 Displacement (mL) 2438
 Rated power (kW/rpm) 102/4600~5000
 Maximum torque (N·m/rpm) 210/2600~3200
 Transmission Transmission model Yancheng Zomax (ZM025A)
 Fuel Tank and Fuel Fuel type Gasoline
 Fuel tank volume (L) 70
 Steering System Steering assist Hydraulic power assisted steering, pinion-and-rack type
 Brake System Type of brake system Hydraulic double-circuit vacuum boosting
 Brake assist system Electronic ABS+EBD brake assist system (ABS + braking force distribution system)
 Parking brake Side parking brake structure, with hand control acting on rear wheels
 Suspension System Front suspension structure Front independent, torsion bar
 Rear suspension structure Non-independent, steel plate, 5 springs
 Wheel Model 195R/15C;195R/15LT
 Quantity 5
 Number of Seats Number of Seats 5-9
 Note: Other configuration details are seen in the sales configuration table.
 Special Configuration of the Kingo Negative Pressure Ambulance (Type I/Type II)
 Function Equipment Equipment Description Quantity Used
 Alarm Lamp System Alarm lamp Strip alarm lamp One set
 Central Power Distribution System Multifunctional power supply control system It supports two power supply modes, external power supply (to be connected with utility power) and vehicle-mounted intelligent inverter power supply system, capable of automatic switching between 12 V DC and 220 V AC power supplies. One set
 Medicine Cabinet System Medicine cabinet Light-weight environmental protection material One set
 Oxygen cylinder cabinet Light-weight environmental protection material One set
 Combined cabinet Light-weight environmental protection material One set
 Medical Floor Medical floor leather Resistant to acid, alkali, fire, skidding, static electricity One set
 Specialized Medical Equipment Oxygen cylinder 10L Two sets
 Sputum aspirator One set
 Sphygmomanometer One set
 Ultraviolet disinfection lamp One set
 Oxygen supply system One set
 Stretcher System Deluxe automatic boarding stretcher + automatic boarding platform (including shovel stretcher) Patient transferring One set
 Medical Cabin Lighting System Working lamp One set
 Stretcher-type Negative Pressure Isolation Cabin Stretcher-type Negative Pressure Isolation Cabin
 Power supply: rated voltage of AC 220 V, 50 HZ, internal power supply DC 12 V, input power of 50 VA. Filtration power: filtration efficiency ?99.99% for 0.3 ?m particulate aerosol. Negative pressure: A negative pressure of not less than 15 Pa shall be established within 2 min when there is passenger in

the ambulance. Ventilation rate: 75 L/min. Effective power supply duration: lithium battery power supply, 2 h. Noise: 72 dB(A). One set

Negative Pressure System Fan system Exhaust air rate: 200 m³/h-600 m³/h, 220 V, 300 W to ensure optimal ventilation efficiency in the medical cabin, and to minimize the probability of cross infection among medical staff during the process of treating and transferring patients with infectious diseases. One set (Type II only)

Filtration system Filtration power: filtration efficiency 99.99% for 0.3 μm particulate aerosol (the national standard requiring 99.97%). The air in the van will be discharged after bio-safety disposal.

Standard Configuration of the Kingo Negative Pressure Ambulance (Type I/Type II)

Item Vehicle Model Parameters

Vehicle Dimensions Length × width × height (mm) 5470×1885×2440; 5570×1885×2440 (with rear step)

Wheelbase (mm) 3110

Front/rear wheel track (mm) 1635/1745

Internal Dimensions of Medical Cabin Length × width × height (mm) 3360×1700×1570

Weight Parameters Curb weight (kg) 2150

Gross mass (kg) 3380

Trafficability Approach angle/departure angle (°) 17/18/17/17

Minimum turning diameter (m) 11.7

Dynamic Performance Maximum speed (km/h) 150

Maximum gradeability (%) 30%

Engine Engine Model Mianyang Xincheng 4RB2

OBD Standard configuration

Emission standard China V for light vehicle

Operating mode In-line 4-cylinder 8-valve, variable valve timing technology

Displacement (mL) 2438

Rated power (kW/rpm) 102/4600~5000

Maximum torque (N·m/rpm) 210/2600~3200

Transmission Transmission model Yancheng Zomax (ZM025A)

Fuel Tank and Fuel Fuel type Gasoline

Fuel tank volume (L) 70

Steering System Steering assist Hydraulic power assisted steering, pinion-and-rack type

Brake System Type of brake system Hydraulic double-circuit vacuum boosting

Brake assist system Electronic ABS+EBD brake assist system (ABS + braking force distribution system)

Parking brake Side parking brake structure, with hand control acting on rear wheels

Suspension System Front suspension structure Front independent, torsion bar

Rear suspension structure Non-independent, steel plate, 5 springs

Wheel Model 195R/15C;195R/15LT

Quantity 5

Number of Seats Number of Seats 5-9

Note: Other configuration details are seen in the sales configuration table.

Special Configuration of the Kingo Negative Pressure Ambulance (Type I/Type II)

Function Equipment Equipment Description Quantity Used

Alarm Lamp System Alarm lamp Strip alarm lamp One set

Central Power Distribution System Multifunctional power supply control system It supports two power supply modes, external power supply (to be connected with utility power) and vehicle-mounted intelligent inverter power supply system, capable of automatic switching between 12 V DC and 220 V

AC power supplies. One set
Medicine Cabinet System Medicine cabinet Light-weight environmental protection material One set
Oxygen cylinder cabinet Light-weight environmental protection material One set
Combined cabinet Light-weight environmental protection material One set
Medical Floor Medical floor leather Resistant to acid, alkali, fire, skidding, static electricity One set
Specialized Medical Equipment Oxygen cylinder 10L Two sets
Sputum aspirator One set
Sphygmomanometer One set
Ultraviolet disinfection lamp One set
Oxygen supply system One set
Stretcher System Deluxe automatic boarding stretcher + automatic boarding platform (including shovel stretcher) Patient transferring One set
Medical Cabin Lighting System Working lamp One set
Stretcher-type Negative Pressure Isolation Cabin Stretcher-type Negative Pressure Isolation Cabin
Power supply: rated voltage of AC 220 V, 50 HZ, internal power supply DC 12 V, input power of 50 VA. Filtration power: filtration efficiency ≥99.99% for 0.3 μm particulate aerosol. Negative pressure: A negative pressure of not less than 15 Pa shall be established within 2 min when there is passenger in the ambulance. Ventilation rate: ≥75 L/min. Effective power supply duration: lithium battery power supply, ≥2 h. Noise: ≤72 dB(A). One set
Negative Pressure System Fan system Exhaust air rate: 200 m³/h-600 m³/h, 220 V, 300 W to ensure optimal ventilation efficiency in the medical cabin, and to minimize the probability of cross infection among medical staff during the process of treating and transferring patients with infectious diseases. One set (Type II only)
Filtration system Filtration power: filtration efficiency ≥99.99% for 0.3 μm particulate aerosol (the national standard requiring ≥99.97%). The air in the van will be discharged after bio-safety disposal.