

PERKINS DIESEL GENSET-OPEN TYPE

Specifications :

Price	\$800-\$20000
Brand Name	CHINLION
Model Number	CL-P24GF
Place of Origin	CHINA
Min.Order Quantity	1
Payment Terms	T/T,L/C
Supply Ability	100UNITS
Delivery Detail	30DAYS
Packaging Details	WOOD

Detail Introduction :

PERKINS 50Hz

Genset model	Output power		Engine model	Bore*Stroke	CYL	Displacement	Lube	Fuel consumption	
	KW	KVA		(mm)		?L)	?L)	g/kw.h	
CL-P7GF	7	8.75	403A-11G1	77*87	3	0.99	4.9	248	12
CL-P10GF	10	12.5	403A-15G1	84*90	3	1.62	6	264	12
CL-P12GF	12	15	403A-15G2	84*90	3	1.49	6	264	12
CL-P16GF	16	20	404A-22G1	84*100	4	2.2	10.6	237	15
CL-P50GF	50	62.5	1104A-44TG1	105*127	4	4.4	8.3	208	22
CL-P64GF	64	80	1104A-44TG2	105*127	4	4.4	8.3	208	23
CL-P80GF	80	100	1104C-44TAG2	100*127	4	4.4	8.3	208	24
CL-P110GF	110	137.5	1106A-70TG1	100*120	6	7.01	8.3	199	24
CL-P120GF	120	150	1106A-70TAG2	105*135	6	7.01	19	208	26
CL-P140GF	140	175	1106A-70TAG3	105*135	6	7.01	19	206	27
CL-P160GF	160	200	1106A-70TAG4	105*135	6	7.01	19	220	30
CL-P24GF	24	30	1103A-33G	105*127	3	3.3	8.3	211	17

CL-P36GF	36	45	1103A-33TG1	105*127	3	3.3	8.3	211	20
CL-P50GF	50	62.5	1103A-33TG2	105*127	3	3.3	8.3	215	22
CL-P180GF	180	225	1506A-E88TAG2	112*149	6	8.8	41	200	30
CL-P200GF	200	250	1506A-E88TAG3	112*149	6	8.8	41	200	31
CL-P220GF	220	275	1506A-E88TAG4	112*149	6	8.8	41	198	31
CL-P240GF	240	300	1506A-E88TAG5	112*149	6	8.8	41	198	31
CL-P280GF	280	350	2206C-E13TAG2	130*157	6	12.5	40	209	36
CL-P320GF	320	400	2206C-E13TAG3	130*157	6	12.5	40	206	36
CL-P360GF	360	450	2506C-E15TAG1	137*171	6	15.2	62	211	40
CL-P400GF	400	500	2506C-E15TAG2	137*171	6	15.2	62	211	40
CL-P480GF	480	600	2806C-E18TAG1A	145*183	6	18.1	62	216	41
CL-P520GF	520	650	2806A-E18TAG2	145*183	6	18.1	62	202	42
CL-P600GF	600	750	4006-23TAG2A	160*190	6	22.9	113	209	45
CL-P640GF	640	800	4006-23TAG3A	160*190	6	22.9	113	209	46
CL-P720GF	720	900	4008TAG1A	160*190	8	30.5	153	206	48
CL-P800GF	800	1000	4008TAG2A	160*190	8	30.5	153	206	49
CL-P1000GF	1000	1250	4012-46TWG2A	160*190	12	45.8	177	212	53
CL-P1100GF	1100	1375	4012-46TWG3A	160*190	12	45.8	159	212	53
CL-P1200GF	1200	1500	4012-46TAG2A	160*190	12	45.8	177	212	54
CL-P1360GF	1360	1700	4012-46TAG3A	160*190	12	45.8	177	212	55
CL-P1480GF	1480	1850	4016TAG1A	160*190	16	61.1	237	205	57
CL-P1600GF	1600	2000	4016TAG2A	160*190	16	61.1	237	208	58
CL-P1800GF	1800	2250	4016-61TRG3	160*190	16	61.1	237	205	59

Model with “E” are standby power gensets. China 0# light diesel or higher are recommended for sutech gensets with oil water separator to ensure purity fuel. Suggest to adopting API CF or higher oil, temperature/viscosity of 15W-40. This parameter table is only for reference and no notice any more if have change.

PERKINS 60Hz

Model	Output			Consumption	Engine	Cylinders	Vol	Dimension(mm)
	kVA	kW	A	Diesel (l/hr)			L	(L×W×H)
CL-P11GF	11	8.8	15.84	3.1	403D-11G	3	1.1	1400*760*920
CL-P13GFE	13	10.4	18.72					
CL-P16GF	16	12.8	23.04	4.3	403D-15G	3	1.5	1400*760*980
CL-P18GFE	18	14.4	25.92					
CL-P24GF	24	19.2	34.56	6.2	404D-22G	4	2.2	1500*900*1150
CL-P26GFE	26	20.8	37.44					
CL-P35GF	35	28	50.4	8.6	1103A-33G	3	3.3	1750*900*1120
CL-P40GFE	40	32	57.6					
CL-P50GF	50	40	72	12.9	1103A-33TG1	3	3.3	1750*900*1120
CL-P60GFE	60	48	86.4					
CL-P70GF	70	56	100.8	16.6	1103A-33TG2	3	3.3	1750*900*1120
CL-P80GFE	80	64	115.2					
CL-P75GF	75	60	108	17.8	1104A-44TG1	4	4.4	1860*900*1250
CL-P85GFE	85	68	122.4					
CL-P90GF	90	72	129.6	22.3	1104A-44TG2	4	4.4	1860*900*1250
CL-P100GFE	100	80	144					
CL-P110GF	110	88	158.4	26.9	1104C-44TAG2	4	4.4	2150*1000*1360
CL-P125GFE	125	100	180					
CL-P155GF	155	124	223.2	35.22	1106A-70TG1	6	6	2300*1100*1500
CL-P170GFE	170	136	244.8					
CL-P200GF	200	160	288	46.4	1106A-70TAG3	6	6	2300*1100*1650
CL-P220GFE	220	176	316.8					
CL-P230GF	230	184	331.2	54	1506A-E88TAG1	6	8.8	2600*1250*1180
CL-P255GFE	250	200	360					
CL-P250GF	250	200	360	56	1506A-E88TAG2	6	8.8	2600*1250*1180
CL-P275GFE	275	220	396					
CL-P400GF	400	320	576	84	2206C-E13TAG2	6	12.5	3100*1400*2000

CL-P440GFE	440	352	633.6					
CL-P500GF	500	400	720	100	2506C-E15TAG1	6	15.2	3400*1420*2180
CL-P550GFE	550	440	792					
CL-P550GF	550	440	792	121	2506C-E15TAG3	6	15.2	3400*1420*2180
CL-P625GFE	625	500	900					
CL-P625GF	625	500	900	130	2806A-E18TAG1A	6	18.1	3580*1700*2180
CL-P700GFE	700	560	1008					
CL-P680GF	680	544	979.2	145	2806A-E18TAG3	6	18.1	3580*1700*2180
CL-P750GFE	750	600	1080					
CL-P800GF	800	640	1152	200	4006-23TAG3A	6	23	4050*2000**2200
CL-P900GFE	900	720	1296					
CL-P1000GF	1000	800	1440	224	4008TAG2	8	30.6	4850*2060*2450
CL-P1100GFE	1100	880	1584					
CL-P1250GF	1250	1000	1800	266	4012-46TWG2A	12	45.8	4750*1860*2330
CL-P1400GFE	1400	1120	2016					
CL-P1500GF	1500	1200	2160	315	4012-46TAG2A	12	45.8	5060*2200*2400
CL-P1650GFE	1650	1320	2376					
CL-P1700GF	1700	1360	2448	356	4012-46TAG3A	12	45.8	5190*2200*2750
CL-P1880GFE	1880	1504	2707.2					

Model with “E” are standby power gensets. China 0# light diesel or higher are recommended for sutech gensets with oil water separator to ensure purity fuel. Suggest to adopting API CF or higher oil, temperature/viscosity of 15W-40. This parameter table is only for reference and no notice any more if have change.