

## **Septic Cleaning Truck**

**Specifications:** 

Price	20000
Brand Name	CHINLION
Model Number	CHL5070GXEDG6
Place of Origin	CHINA
Min.Order Quantity	1
Payment Terms	T/T
Supply Ability	100UNITS
Delivery Detail	30DAYS
Packaging Details	RORO VESSEL

## Detail Introduction: PARAMETERS

Parameters	FLM5070GXEDG6
Chassis Model	EQ1075SJ3CDF
Emission Standard	China VI
Suction Range (m)	?6
Tank Volume (m³)	?4.3
Full Tank Suction Time (min)	?4
Payload (kg)	3300
Dimension (L x W x H) (mm)	5935×2000×2520

## **FEATURES**

The truck adopts a circular container that matches with an integrally pressed butterfly head, providing better pressure bearing performance.

The container is designed with a double hole cover, which makes cleaning and maintenance faster more convenient. Both sides are equipped with large toolboxes, with a total volume of 0.8 cubic meters (the toolbox on the right is used to place the suction tube). The sewage tank liquid level display adopts an imported liquid level display device, which is easy to observe, easy to disassemble, easy to clean, and easy to maintain.

The discharge port adopts a flange-connected stainless steel floating ball valve, which can self-compensate the gap and maintain good long-term sealing. It is driven by an electric push rod, which can be controlled in the cab and at the rear of the vehicle.



The suction port adopts a suction and discharge dual-purpose infusion device, which can rotate 360 degrees. It also has a quick dredging and cleaning window, which can be used for extraction operations at the same time, with a wider range of operations and more convenient cleaning. The truck is equipped with multiple safety devices such as the anti-overflow valve, the overpressure safety valve, and a full tank alarm. It can effectively prevent the tank from over-sucking, or development of high pressure during reverse discharge, to ensure a normal operation of the vacuum pump and personal safety of the staff.