

Wheeled armored anti-riot disperse vehicle

Specifications:

Price	200000
Brand Name	CHINLION
Model Number	CHL1003
Place of Origin	CHINA
Min.Order Quantity	1
Payment Terms	T/T
Supply Ability	100
Delivery Detail	40DAYS
Packaging Details	RORO VESSEL

Detail Introduction:

Chassis 4x4 military off-road chassis

Chassis 4x4 military off-road chassis		
engine model	Cummins ISDE180-30 200-30 EFI, Turbo Jade, Bosch Common Rail (HPCR) Mediu Engine	
engine maximum power	136KW72500r/MN(4.5L)180hp 147kw(optional)	
maximum torque	650/1200-1700n.m/mp	
fuel consumption	20L/100km	
number of vehicle occupants	2+5 people	
Vehicle curb weight	5500 g	
Maximum loading mass	100 g	
total mass	6500 g	
Maximum trailer weight	1500kg	



Outline Dimensions (LxWxH)	5360mmx2320mmX2640mm		
vehicle maximum speed	115 km/h		
Maximum grade	Three 60%		
Turning diameter	15m		
wading depth	0.8 meters without preparation, 12 meters with preparation		
Fuel tank capacity	120L		
Maximum mileage	600km		
weapon system	2 anti-riot CS strong stimulation dry powder spray dispersing guns; 2 38mm 9-tube from 0 to 150m in front of the car, horizontal coverage ±70°		tube a
Protection performance The whole car can resist 56-type 7.62mm ordinary bullets			
drive form		4X4	
number of passengers		2+2	
total mass		5500kg	
Maximum Outline Dimensions (LxWxH) Wheelbase		5720mmX 200mmX 2650mm	
		3310mm	
track approach angle		Front wheel 1670mm Rear wheel 1670mm	
		33^	
departure angle		30°	
Minimum ground clearance		280mm	

100km/h

32°

Maximum Speed Maximum Gradient Minimum Turning Diameter Wading Depth



15m 0.75m	
Maximum mileage	850km (mailbox capacity 124L)
engine model	SOFIM8142.45 inline 4-cylinder, water-cooled, direct injection, turbocharged, intercooled diesel engine 3.01L
Exhaust volume	
engine power	95km/3600r/min
engine maximum torque	269N.m/1900r/min
Tire Specifications Air Conditioning Power Supply Voltage	255/00R16 126/ 124K Off-Road Radial Bulletproof Tire
	8000kca/h
	24V