

150KVA 50Hz CUMMINS sound proof generator set

Specifications :

Price	400-15000USD
Brand Name	Cummins
Model Number	CHLCS150S
Place of Origin	CHINA
Min.Order Quantity	1
Payment Terms	T/T?L/C
Supply Ability	100UNITS
Delivery Detail	30DAYS
Packaging Details	WOOD

Detail Introduction :

Genset Power	136.25
Model Type	Soundproofed
Engine Model	QSB5-G6
Alternator Model	UCI274E
Control System Model	PLC-7420
General Data	CHLCS150S
Manufacturer	CHINLION
Prime Power?kVA?	136.25
Standby Power?kVA?	149.88
Prime Power?kW?	109.0
Standby Power?kW?	119.9
Power Factor	0.8
Frequency?Hz?	50.0
Phase	3.0

Wires	5.0
Volatage?V?	380/400/415/440
Fuel Consumption (75%load)?L/h?	27.0
Fuel Consumption (100%load)?L/h?	31.0
Fuel Tank Capacity?L?	300.0
Oil Consumption?L/h?	0.7
Displacement?L?	4.5
Noise Level@1m?dBA?	80.9
Noise Level@7m?dBA?	74.5
Dimensions L*W*H?mm?	3350*1150*1750
Dry Weight?Kg?	2030.0
Type of Fuel	0# or ASTM2
Type of Oil	CF4/SG15W-40
Machine Body	
Model Type	Soundproofed
Length?mm?	3350.0
Width?mm?	1150.0
Height?mm?	1750.0
Protection Level	IP54
Standard Package	?
current	
380V / 400V / 415V / 440V	207/197/190/179
208V/220V / 230V / 240V	/
416V / 440V / 460V / 480V	/
6000V~6600V	/
10000V~13800V	/
Genset Control Cabinet	

Control Model	PLC-7420
Starting Type	Auto/Manual
Screen Dimension?mm?	240*181*41.7
Observation Window and Control Door	?
Protection Level	IP56
Battery Charger	?
Breaker	ABB 250A
Poles	3.0
Breaker Control Mode	Manual
Leak Protection Device	X
Connection Type of External Cable	Connector terminal
Cable Line Slot	X
Genset Internal Connection Type	X
Fuel System	
Fuel Tank	
Fuel Tank Capacity?L?	300.0
Injection System	Direct injection
Recommended Fuel Type	0# or ASTM2
Fuel Tank Type	Double-layer
Can be connected to external fuel filling device	?
Fuel Tank Drain	?
Fuel Level Control Panel Display	?
Fuel Level Gauge	?
Auto Refilling Diesel System	X
Oil Pan	X
Fuel Three-way Valve	?
Conditions	

Ambient Temperature ?°C?	40.0
Barometric Pressure ?kPa?	100.0
Relative Humidity	?80%
Altitude ?m?	?1000